

SPECIFICATIONS



TREK LINE		TREK 2.2	TREK 4	TREK 5.5	TREK 7.5	TREK 11	TREK 15	TREK 18.5	TREK 22	TREK 30	TREK 37	TREK 45	TREK 55	TREK 75
Flow Model L - 7 bar*	m ³ /h	–	–	–	68	99	145	179	208	278	358	428	566	779
	m ³ /min	–	–	–	1,13	1,65	2,42	2,98	3,47	4,63	5,97	7,13	9,43	12,98
Flow Model H - 8 bar*	m ³ /h	–	–	–	64	95	137	169	197	263	341	407	535	733
	m ³ /min	–	–	–	1,07	1,58	2,28	2,82	3,28	4,38	5,68	6,78	8,92	12,22
Flow Model HH - 10 bar*	m ³ /h	17,4	29,1	41,4	57	86	121	149	177	232	306	365	473	642
	m ³ /min	0,29	0,49	0,69	0,95	1,43	2,02	2,48	2,95	3,87	5,10	6,08	7,88	10,70
Flow Model XH - 12 bar*	m ³ /h	–	–	–	–	70	89	129	156	204	265	306	400	–
	m ³ /min	–	–	–	–	1,17	1,48	2,15	2,60	3,40	4,42	5,10	6,67	–
Motor Power	kW	2,2	4	5,5	7,5	11	15	18,5	22	30	37	45	55	75
Noise Level	dB(A)	70	73	75	70	71	72	73	74	74	74	74	78	78
Dimensions (LxIxh)	mm	750	750	750	1000	1000	1280	1200	1200	1200	1500	1500	1846	1846
		x 1244 x 1320	x 1244 x 1320	x 1244 x 1320	x 680 x 1335	x 680 x 1335	x 680 x 1335	x 800 x 1490	x 800 x 1490	x 800 x 1490	x 950 x 1760	x 950 x 1760	x 1360 x 1940	x 1360 x 1940
Total Weight	kg	249	268	268	300	350	360	520	540	615	810	875	1435	1645
Air outlet diameter	BSP	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	2"

TREK-V LINE		TREK-V 18.5	TREK-V 22	TREK-V 30	TREK-V 37	TREK-V 45	TREK-V 55	TREK-V 75
Flow Model L - 7 bar*	m ³ /h	179	208	278	358	428	566	779
	m ³ /min	2,98	3,47	4,63	5,97	7,13	9,43	12,98
Flow Model H - 8 bar*	m ³ /h	169	197	263	341	407	535	733
	m ³ /min	2,82	3,28	4,38	5,68	6,78	8,92	12,22
Flow Model HH - 10 bar*	m ³ /h	149	177	–	306	365	473	642
	m ³ /min	2,48	2,95	–	5,10	6,08	7,88	10,70
Flow Model XH - 12 bar*	m ³ /h	–	156	–	265	306	–	–
	m ³ /min	–	2,60	–	4,42	5,10	–	–
Motor Power	kW	18,5	22	30	37	45	55	75
Noise Level	dB(A)	73	74	74	74	74	78	78
Dimensions (LxIxh)	mm	1550 x 900 x 1530	1550 x 900 x 1530	1550 x 900 x 1530	1800 x 950 x 1760	1800 x 950 x 1760	1900 x 1360 x 1940	1900 x 1360 x 1940
		575	595	730	925	1020	1520	1735
Air outlet diameter	BSP	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	2"

* Standard ISO 1217



THE GREEN INNOVATOR

SULLAIR EUROPE Zone des Granges - B.P. 82 - F - 42602 MONTBRISON CEDEX
 Tel +33 (0)4 77 96 84 70 - Fax +33 (0)4 77 96 84 99
 sullair.europe@sullaireurope.com - www.sullair.com

EQUIPMENT

Trek *line*

Nothing but pure air.



TREK LINE		TREK 2.2	TREK 4	TREK 5.5	TREK 7.5	TREK 11	TREK 15	TREK 18.5	TREK 22	TREK 30	TREK 37	TREK 45	TREK 55	TREK 75
MOTOR	IP55	X	X	X	X	X	X	X	X	X	X	X	X	X
	400 volts Tri	X	X	X	X	X	X	X	X	X	X	X	X	X
	Direct Starter	X	X	X	—	—	—	—	—	—	—	—	—	—
	Starter Y/Δ	—	—	—	X	X	X	X	X	X	X	X	X	X
SULLUBE LUBRICANT		X	X	X	X	X	X	X	X	X	X	X	X	X
AIR COOLING		X	X	X	X	X	X	X	X	X	X	X	X	X
CONDENSATE SEPARATOR		—	—	—	Option	Option	Option	X	X	X	X	X	X	X
ON A 270 LT TANK		X	X	X	—	—	—	—	—	—	—	—	—	—
MICROVISOR 2		—	—	—	Option	Option	Option	Option	Option	Option	X	X	X	X
VARIABLE SPEED WITH MICROVISOR 2-V		—	—	—	—	—	—	Option	Option	Option	Option	Option	Option	Option